



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Tatum LED Flush Mount TTMF Series

Features

This low profile design provides a dramatic look and features an edge-lit panel construction. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel finish.

Diffuser

White acrylic.

Electrical

D1 Driver

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Input 120-277 VAC 60 Hz. LED driver is dimmable 0-10V DC.

LED

Integrated LED modules capable of producing:
 17.5W = 1400 source lumens, 733 delivered lumens
 31W = 2600 source lumen, 1682 delivered lumens
 3000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
 subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	Delivered Lumens	CCT	DIA.	D
TTMF1214L30D1SN	17.5W	1400	753	3000K	12"	2-3/4"
TTMF1214L30D2SN	17.5W	1400	753	3000K	12"	2-3/4"
TTMF1626L30D1SN	31W	2600	1682	3000K	16"	2-3/4"
TTMF1626L30D2SN	31W	2600	1682	3000K	16"	2-3/4"

