# AMIR - MIRAGE™ CONVECTOR



## **MIRAGE**<sup>™</sup>



## THE MOST DISCREET ON THE MARKET!

The Mirage convector has a unique, modern and discreet look and offers unquestionable efficiency. Available with or without an ultraprecise integrated electronic thermostat and in several voltages, the Mirage is suitable for rooms in homes or businesses. With its simple facade and elegant design, the Mirage blends in with any decor.

- BLENDS IN WITH ANY DECOR
- STURDY ONE-PIECE FRONT PANEL
- TOTALLY QUIET
- BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL)
   WITH BACKLIT SCREEN
- ADAPTS TO MULTIPLE MARKETS AVAILABLE IN 120 V, 208 V, 240 V, 277 V AND 480 V

#### **COLORS**

- · standard: white
- Orora (optional): refer to www.stelpro.com/en-US/Orora

#### **FINISH**

• epoxy-polyester powdercoat

#### **MANUFACTURING**

- · 20-gauge steel cabinet and front
- the cabinet height improves the chimney effect
- bottom air intake and top air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (AMIR1501P model)

#### **ELEMENTS**

 two stainless steel tubular sheathed elements insulated with nylon sleeves reducing expansion and contraction noises

#### CONTROL

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)
- automatic temperature lowering at night (Automatic mode)
- maximum temperature setpoint lock option (Security mode)

#### **INSTALLATION**

- · surface mounted only
- · wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

#### WARRANTY

five years, \*three years on electronic components



**BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE** FOR THE 120 V TO 240 V MODELS



#### **IDEAL FOR:**

kitchen, living room, bedroom, basement, commercial space, office





	TECHN	IICAL SF	PECIFIC	CATIONS	3		
BUILT-IN THERMOSTAT	WITHOUT THERMOSTAT	POWER		VOLTAGE	HEIGHT	LENGTH	WEIGHT
CODE	CODE	WATTS	BTU/H	VOLTS	IN.	IN.	LB
AMIR0501W	AMIR0501WCW	500	2048	120	18	17 1/2	11.75
AMIR0508W	AMIR0508WCW	500	2048	208	18	17 1/2	11.75
AMIR0502W	AMIR0502WCW	500/375	2048	240/208	18	17 1/2	11.75
	AMIR0507WCW	500	2048	277	18	17 1/2	11.75
AMIR1001W	AMIR1001WCW	1000	3413	120	18	23 1/2	14.75
AMIR1008W	AMIR1008WCW	1000	3413	208	18	23 1/2	14.75
AMIR1002W	AMIR1002WCW	1000/750	3413	240/208	18	23 1/2	14.75
	AMIR1007WCW	1000	3413	277	18	23 1/2	14.75
	AMIR1005WCW	1000	3413	480	18	23 1/2	14.75
AMIR1501W	AMIR1501WCW	1500	5119	120	18	29 1/2	17.75
AMIR1508W	AMIR1508WCW	1500	5119	208	18	29 1/2	17.75
AMIR1502W	AMIR1502WCW	1500/1125	5119	240/208	18	29 1/2	17.75
	AMIR1507WCW	1500	5119	277	18	29 1/2	17.75
	AMIR1505WCW	1500	5119	480	18	29 1/2	17.75
AMIR2008W	AMIR2008WCW	2000	6825	208	18	35 1/2	20.75
AMIR2002W	AMIR2002WCW	2000/1500	6825	240/208	18	35 1/2	20.75
	AMIR2007WCW	2000	6825	277	18	35 1/2	20.75
	AMIR2005WCW	2000	6825	480	18	35 1/2	20.75
	MODI	EL WITH 120 V PLU	G (RESIDENTIAL	OUTLET)			
AMIR1501PW*		1500	5119	120	18	29 1/2	17.75

Consult the optional color chart and contact your Stelpro representative for all other colors.

Mechanical wall thermostats are not compatible with the without thermostat model (WC) – electronic thermostat is required.

\* Available in white only

--- not available

ACCESSORIES				
PRODUCT	DESCRIPTION			
MIRRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]			
MIRRE156*	built-in electronic low voltage relay [6 A @ 600 V]			
MIRRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]			

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal. \* Factory installed

### **TECHNICAL DRAWINGS**

