

Project: _____
 Part#: _____
 Type: _____

4" SnapTrim Adjustable Downlight

5CCT Selectable: 27/30/35/40/50K



EnVision LED has developed a line of 4" SnapTrim Downlights that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. By reducing material cost and installation time, the EnVision SnapTrim is the ideal retrofit or new construction recessed lighting solution yet. Simply cut a hole in the ceiling, power the J-Box to the wall switch, and "snap" the trim flush. Now available with 5CCT color changing technology! Switch from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

Detail Specifications:

- IP65 Wet Location Rated
- CRI >93 COB LED Chip, R9>50
- Input Voltage: 120V (108-132V Range)
- 40° Beam Angle
- Operating Temperature: 0°F ~ +113°F
- PF >0.9
- 2.5kV Ringwave Surge Protection
- Cut Out Dimension: 4-1/4"
- Triac and ELV Dimmable down to 5%

Applications:

- Residential or Commercial Downlighting
- New Construction or Remodel use
- General recessed lighting
- Drywall, drop ceiling, sloped ceiling

Product Information:

- 5CCT Selectable: 27/30/35/40/50K
- Available in white, black, and brushed nickel finish
- SnapTrim Canless: Spring clips with remote j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance
- 360° Adjustable gimbal with 30° tilt

Mounting:

- No can needed in remodel applications, tension clip springs clamp into 1/2" to 1.5" thick ceiling
- Pre-wired junction box with circuit wiring built in (3 in / 3 out)
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)

Certifications:

- ETL Listed for USA and CA
- Energy Star Certifies
- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

Whats Included?:

- LED Module
- Junction Box
- Cut Out Template
- Mounting Screws
- Installation Guide

LED - DL J B X - A D J - 4 - 1 2 W - 5 C C T - Finish _ Accessories _ EMB _ Warranty

1 Product	2 Size/Watts	3 Color	4 Finish	5 Accessories	6 EMB	7 Warranty
LED-DLJBX-ADJ	4-12W 4 Inch / 12W / 750lm	5CCT 27/30/35/40/50K	WH White BLK Black BN Brushed Nickel	(Blank) C4-JBX-RI CUNV-NC-ICAT JBX-EXT-6-2PIN JBX-EXT-10-2PIN JBX-EXT-6-TRI JBX-EXT-10-TRI	None 4" Rough-in Plate Universal Pre-Mounting Plate 6" Extension Cable 10" Extension Cable 6" Extension Cable (TRI) 10" Extension Cable (TRI)	(Blank) 5 Years (incl.) 10YR 10 Years

Specs and model numbers are subject to change with or without notice

FEATURES

Durable Construction

High quality aluminum trim and heat sync

Adjustable Trim

30°Tilt with 360° Rotation

5CCT Selectable

Choose between 5 different color temps in one single fixture

Selectable color temps:
2700K/3000K/3500K
4000K/5000K/

Drywall Clip

Eliminates the need for a recessed can. Clips right into the dry wall



Hole Cut Size **4 3/8" (105~108mm)**

OPTIONAL ACCESSORIES



CUNV-NC-ICAT

New Construction Plate


Makes new construction installation easier. Universal plate compatible for 2", 4", 6" trims with J-Boxes.



C4-JBX-RI

4" Rough-In Plate

Make installation even easier with this rough-in plate.



**JBX-JUMP-
(4'/10'/20')**

Connector Extension Cord

Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.

Accessory Model	Description
CUNV-NC-ICAT	2/4/6" New Construction Plate
C4-JBX-RI	4" Rough-In Plate
JBX-JUMP-4'	4' Connector Extension Cord
JBX-JUMP-6'	6' Connector Extension Cord
JBX-JUMP-10'	10' Connector Extension Cord

DIMMER COMPATIBILITY				
Brand	Series	Model	Load	Dimmability
Lutron	Ariadni	AYCL-153P	150W	OK
	Diva	DV-600PR	600W	OK
	Diva	DVCL-153P	150W	OK
	Maestro	MACL-153MH	600W	OK
	Maestro Wireless	MRF2-6CL	150W	OK
	Rotary	D-600P	600W	OK
	Electronic(ELV)	NTELV-300P	600W	OK
	Skylark	S-600P	600W	OK
	Skylark Contour	CT-600P	600W	OK
	Skylark Contour	CTCL-153P	150W	OK
	Toggler	TG-600P	600W	OK
Toggler	TGCL-153P	150W	OK	
Leviton	Sureslide	6633	600W	OK
	Sureslide Decora	6674	600W	20-100%
	Trimatron	6602	600W	20-100%
	ILLVMATECH	IPL06	600W	OK
Legrand	Adorne	ADTP703TU	700W	20-100%
	Harmony	H703PTW	700W	OK
Cooper	Aspire	9540	1000W	OK
	Devine	DAL06P	300W	OK

DIMENSIONS

