

# 1007-XP-150-CART- 515-XP

1007-XP-150 LED WORKLIGHT CART w/100 FT 14/3 BLK  
SOOW AND UGP-15231 XP PLUG



## Key features



- cETLus listed lamp
- Heavy duty, light weight, spark resistant aluminum frame
- Bolt on lifting eyes (Optional)
- Cord management bracket
- Class I, Division 1, Groups C, D
- Class I, Division 2, Groups A,B,C,D
- Class II, Division 1, Groups E,F,G
- Class II, Division 2, Groups E,F,G
- Class III
- NEMA 4X, IP66
- T3 temperature rating
- High efficacy: up to 140lm/W
- CRI>70
- Copper free aluminum
- High vibration resistance
- Ambient temperature range: -40°C to 60°C

### Ideal Application

Portable Mobile Lighting for Oil & Gas Industries, Distilleries, Paint Manufacturing, Pumping Stations, Mining, Vessel Lighting, High Humidity Areas, High Temperature Locations

### Color

Gray

### UPC Code

782862926529

### Country of Origin

USA

## Specifications

<b>Brand</b>	Ericson
<b>Sub Brand / Trademark</b>	Hi-Bay XP on Cart
<b>Category</b>	Hazardous Location Grade
<b>Sub Category</b>	Wide Area Light

## Technical Info

<b>Bulb Type</b>	LED
<b>Lumens</b>	21000
<b>Cable Length</b>	100
<b>Cable</b>	14/3
<b>Cable Type</b>	SOW
<b>Max Amps</b>	1.2
<b>Max Volts</b>	120
<b>Max Watts</b>	150
<b>Primary Cable End</b>	NEMA 5-15 (UGP-15231) Hazardous Location Plug
<b>NEMA Environment</b>	Class I Division 1, Groups C, D • Class I Division 2, Groups A, B, C, D • Class II Division 1 & 2, Groups E, F, G • Class III
<b>Construction</b>	Cast Aluminum & Welded Aluminum Cart

## Standards & Certifications

<b>ETL</b>	ETL Listed Luminaire
<b>cETL</b>	cETL Listed Luminaire

## Shipping & Logistics Info

Pack/Unit Qty	1
HTS code	9405106020
ECCN	EAR99
Gross Weight (lbs)	120.00000
Shipment Packaging Length (in)	26
Warranty	1 Year



Ericson Manufacturing Company  
4323 Hamann Parkway  
Willoughby, OH 44094, USA



1-800-374-2766  
[info@ericson.com](mailto:info@ericson.com)

[ericson.com](https://ericson.com)