

### Product Features:

- Kelvin Adjustable — 3500K, 4000K or 5000K
- Wattage Adjustable
  - 2x4 (30W, 40W or 45W)
  - 2x2 (20W, 30W or 36W)
  - 1x4 (20W, 30W or 40W)
- 1–10V Dimmable
- Optional Emergency Battery Backup

### ADJUSTABLE KELVIN & WATTAGE



IC RATED

### Ordering Guide:

Example Part Number: ES LC-DPS-24-U-P

ESLC	DPS	SIZE	U	P-2
ESLC	TYPE	SIZE	INPUT VOLTAGE	LISTING
	DPS ADJUSTABLE WATTAGE & KELVIN FLAT PANEL	24 (2X4 FLAT PANEL) 22 (2X2 FLAT PANEL) 14 (1X4 FLAT PANEL)	U (120–277 VAC)	P-2 (DLC PREMIUM)

### Accessories (field installed):

EMERGENCY BBU:
EL (EMG BATTERY BACKUP - 90 MIN EMERGENCY EGRESS ILLUMINATION)
MOUNTS:
ESLC-DP-SMF-24-W (2X4 SURFACE MOUNT KIT, WHITE FINISH)
ESLC-DP-SMF-22-W (2X2 SURFACE MOUNT KIT, WHITE FINISH)
ESLC-DP-SMF-14-W (1X4 SURFACE MOUNT KIT, WHITE FINISH)
ESLC-DP-SMF-12-S (2' CABLE SUSPENSION MOUNT KIT)
ESLC-DP-SMF-14-S (4' CABLE SUSPENSION MOUNT KIT)

### Product Specifications:

#### Construction:

White finished aluminum frame. Steel die-formed back enclosure.

#### Optical:

- PMMA lenses over LEDs, PS diffuser
- UGR < 22
- SDCM < 5
- 120° Beam angle

Catalog Data:

2X4 PANEL	ITEM#	ADJUSTABLE WATTAGE	LUMEN OUTPUT	EFFICACY (LM/W)	ADJUSTABLE KELVIN
	ESLC-DPS-24-U-P-2	30W	3,750	125	3500K
			3,825	127	4000K
			3,825	127	5000K
		40W	5,000	125	3500K
			5,100	127	4000K
			5,100	127	5000K
		45W	5,625	125	3500K
			5,738	127	4000K
			5,738	127	5000K

2X2 PANEL	ITEM#	ADJUSTABLE WATTAGE	LUMEN OUTPUT	EFFICACY (LM/W)	ADJUSTABLE KELVIN
	ESLC-DPS-22-U-P-2	20W	2,500	125	3500K
			2,550	127	4000K
			2,550	127	5000K
		30W	3,750	125	3500K
			3,825	127	4000K
			3,825	127	5000K
		36W	4,500	125	3500K
			4,572	127	4000K
			4,572	127	5000K

1X4 PANEL	ITEM#	ADJUSTABLE WATTAGE	LUMEN OUTPUT	EFFICACY (LM/W)	ADJUSTABLE KELVIN
	ESLC-DPS-14-U-P-2	20W	2,500	125	3500K
			2,550	127	4000K
			2,550	127	5000K
		30W	3,750	125	3500K
			3,825	127	4000K
			3,825	127	5000K
		40W	5,000	125	3500K
			5,100	127	4000K
			5,100	127	5000K

Dimensions:

