

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

ST19 LED CLEAR FILAMENT/ VINTAGE LAMP

Filament Series



FxxST19DLED9xx/JA81

VxxST19DLED9xx/JA81

Product Description:

MaxLite's energy-efficient dimmable LED filament ST19 lamp is energy saving decorative lamp designed to reproduce the elegant ambient effect of incandescent lamps for hospitality, restaurant, residential and retail applications.

Features:

- Lumens: 450lm to 1,100lm
- Efficacy (lm/W): 90lm/W to 100lm/W
- Suitable for Wet Locations and for use in Enclosed Luminaires

Applications:

- Pendants
- Decorative lighting fixtures

Dimensions

MODEL NUMBER	L	D
F5ST19DLED9xx/JA81	5.04 inches	2.3 inches
F8ST19DLED9xx/JA81		
F10ST19DLED9xx/JA81		
V5ST19DLED9xx/JA81		
V8ST19DLED9xx/JA81		
V10ST19DLED9xx/JA81		

Ordering Information

FAMILY	WATTAGE	SHAPE	DIMMABILITY	COLOR TEMPERATURE & JA8 LISTING
F= Enclosed Clear Filament	5= 5W 8= 8.5W 10= 10W	ST19= ST19 Shape	DLED= Dimmable LED	922/JA81= 90 CRI, 2200K, JA8 Listing 927/JA81= 90 CRI, 2700K, JA8 Listing 930/JA8= 90 CRI, 3000K, JA8 Listing
V= Enclosed Vintage Filament	5= 5W 8= 8.5W 10= 10W			

Stocked Items

ORDER CODE	MODEL NUMBER	QTY IN CASE	ORDER CODE	MODEL NUMBER	QTY IN CASE	ORDER CODE	MODEL NUMBER	QTY IN CASE
110577	F5ST19DLED922/JA81	50	110579	F10ST19DLED922/JA81	50	110581	V8ST19DLED922/JA81	50
110615	F5ST19DLED927/JA81		110619	F10ST19DLED927/JA81		110623	V8ST19DLED927/JA81	
110616	F5ST19DLED930/JA81		110620	F10ST19DLED930/JA81		110624	V8ST19DLED930/JA81	
110578	F8ST19DLED922/JA81		110580	V5ST19DLED922/JA81		110582	V10ST19DLED922/JA81	
110617	F8ST19DLED927/JA81		110621	V5ST19DLED927/JA81		110625	V10ST19DLED927/JA81	
110618	F8ST19DLED930/JA81		110622	V5ST19DLED930/JA81		110626	V10ST19DLED930/JA81	



3-year standard warranty (further details available at www.maxlite.com/warranties)

ST19 LED CLEAR FILAMENT/ VINTAGE LAMP

Filament Series

Specifications	F5ST19DLED9xx/ JA81	F8ST19DLED9xx/ JA81	F10ST19DLED9xx/ JA81	V5ST19DLED9xx/ JA81	V8ST19DLED9xx/ JA81	V10ST19DLED9xx/ JA81
Shape, Base	ST19, E26			ST19, E26		
Replacement Wattage	40W Inc.	60W Inc.	100W Inc.	40W Inc.	60W Inc.	100W Inc.
Input Wattage (W)	5W	8.5W	10W	5W	8.5W	10W
Lumens Delivered (lm)	450	800	1100	450	765	1000
Nominal Efficacy (lm/W)	90	94	110	90	90	100
CCT	2200K, 2700K, 3000K					
CRI	≥90					
Distribution	320°					
L70 Lumen Maintenance	15,000 Hrs					
Dimming Technology	Triac – Forward Phase					
Dimming Range	10-100%					
Input Voltage	120V AC, 60Hz					
Surge Protection	2.5kV Ringing Wave					
Power Factor	≥0.9					
Diffuser	Clear Glass			Vintage Glass		
Operating Temperature	-4°F to 104°F (-20°C to 40°C)					
Environment	Suitable for Wet Locations and for use in Enclosed Luminaires					
Certifications	cETLus listed, RoHS Compliant, FCC, T20, JA8-2022-E					
Warranty	3 years					

Dimming Compatibility

MANUFACTURER	MODELS
Lutron	DVCL-153PR-GR, CTCL-153PR-WH, MSCL-OP153MH-WH, RCL-153PNLH-WH, TGCL-153PR-WH
Leviton	C22-6672-1CW

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.