

PRODUCT DATA SHEET

GAS BALL VALVES

A CSW Industrials Company

Application

Provide a safety shut off valve for gas lines.

• 0.5 Maximum PSI

Recommended Use

- Natural Gas
- Propane

Characteristics | Features

- Quarter Turn Design
- Standard Port
- 100% Leak Tested
- CSA Tested Listed & Approved



Approvals

Complies to ANSI Z21.15 / CSA 9.1



Packaging

Code	Description	Qty per Case	Lbs per Case	Cubic Feet
Gas Ball Valves				
BS138FL	3/8" O.D. (5/8-18) FLARE X 1/2" FIP GAS VALVE	10	3.31	0.04
BS112F	1/2" O.D. (3/4-16) FLARE X 1/2" FIP GAS VALVE	10	3.66	0.04
BS11516FL	5/8" O.D. (15/16-16) FLARE X 1/2" FIP GAS VALVE	10	3.53	0.06
BS11515FLFIP	5/8" O.D. (15/16-16) FLARE X 3/4" FIP GAS VALVE	5	2.76	0.04
BS112FIP	1/2" FIP X 1/2" FIP GAS VALVE	10	3.20	0.04
BS134FIP	3/4" FIP X 3/4" FIP GAS VALVE	5	2.65	0.04



WARNING • This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.



Limited Warranty

For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au 3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R51047-0923